

TECHNICAL DATA SHEET CHEMPOL® 801-2426

Long oil alkyd

PRODUCT APPLICATION DETAILS

 ${\tt CHEMPOL}^{\circledast}$ 801-2426 is a high solids air-dry soya alkyd for exterior acrylic paints with good gloss and color retention, and ease of brushing.

SALES SPECIFICATIONS

	CHARACTERISTICS	METHODS
Solid content	70 %	-
Viscosity	Z1-Z3 Gardner Holdt	-
Reduced viscosity (50% in Mineral Spirits)	D-F Gardner Holdt	-
Color	8 Gardner	-
Acid value	6 mg KOH/g	-

OTHER CHARACTERISTICS¹

	CHARACTERISTICS	METHODS
Solvent	Mineral spirits/A100	-
Density	7.9 lbs/gal	-
Hydroxyl content	1.5 %	-
Hydroxyl number	50	-

'The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

MARKETS

Coatings & Inks • Industrial Coating

- General Industry
 Wood Furniture



PRODUCT SAFETY

Please refer to the corresponding Safety Data Sheet.

STORAGE AND HANDLING

CHEMPOL® 801-2426 - Packaged products should be stored in a dry indoor location. The material should be stored in the original, unopened and undamaged container at storage temperatures not exceeding 85° F (30° C). Exposure to direct sunlight should be avoided. For assistance with the best practices for bulk shipment storage and handling contact Arkema.

Coating Resins - 2025-05-25 - Page: 2 / 2

Arkema Coating Resins 410 Gregson Dr. Cary, NC 27511 – USA T +1 919 469 6700

Headquarter: Arkema France 51, Esplanade du Général de Gaulle 92800 Puteaux – France T +33 (0)1 49 00 80 80

ARKEMA

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on https://www.arkema.com/global/en/products/product-safety/disclaimer/ which is incorporated herein by reference and made a part hereof. Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the

number 319 632 790

arkema.com