

# TECHNICAL DATA SHEET CHEMPOL<sup>®</sup> 812-0173

Modified alkyd

#### **PRODUCT APPLICATION DETAILS**

<code>CHEMPOL® 812-0173</code> is a rosin-modified linseed oil alkyd resin with fast tack-free and dry-through times, and excellent adhesion, gasoline resistance, and humidity resistance, for use in primers and auto OEM coatings.

# **SALES SPECIFICATIONS**

	CHARACTERISTICS	METHODS
Solid content	65 %	-
Viscosity	X-Z Gardner Holdt	-
Reduced viscosity (50% in n-Butyl Acetate)	E-G	-
Color	17 Gardner	-
Acid value	10 mg KOH/g	-

#### **OTHER CHARACTERISTICS<sup>1</sup>**

	CHARACTERISTICS	METHODS
Solvent	n-Butyl acetate/Xylene 93/7	-
Density	8.8 lbs/gal	-

'The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

#### MARKETS Coatings & Inks

Industrial Coating

- Automotive OEM
- General Industry

# PERFORMANCE BENEFITS

- CHEMPOL® 812-4107 in n-Butyl Acetate
- Fast Free Times and Through Dry
- Excellent Gasoline Resistance
- Excellent AdhesionOutstanding Humidity
- Resistance
- Meets Federal Specifications TT-P-644 and TT-E-515



# FORMULATION GUIDELINES

# **RECOMMENDATIONS OF USE**

Primer Coatings Auto OEM Under-hood Parts General Industrial Coatings

#### **PRODUCT SAFETY**

Please refer to the corresponding Safety Data Sheet.

#### **STORAGE AND HANDLING**

CHEMPOL® 812-0173 - Packaged products should be stored in a dry indoor location. The material should be stored in the original, unopened and undamaged container at storage temperatures not exceeding 85° F (30° C). Exposure to direct sunlight should be avoided. For assistance with the best practices for bulk shipment storage and handling contact Arkema.

Coating Resins - 2025-05-25 - Page: 2 / 2

**Arkema Coating Resins** 410 Gregson Dr. Cary, NC 27511 – USA T +1 919 469 6700 Headquarter: Arkema France 51, Esplanade du Général de Gaulle 92800 Puteaux – France T +33 (0)1 49 00 80 80

ARKEMA

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on https://www.arkema.com/global/en/products/product-safety/disclaimer/ which is incorporated herein by reference and made a part hereof. Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the

Arkema France, a French societe anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

arkema.com