

## TECHNICAL DATA SHEET

# CHEMPOL® 812-4102

*Modified alkyd*

### PRODUCT APPLICATION DETAILS

CHEMPOL® 812-4102 is a rosin-modified linseed oil alkyd with fast tack-free and through-dry times, and excellent moisture, gasoline, and salt spray resistance, for use in primer, drum, storage tank, and auto OEM underhood coatings.

### SALES SPECIFICATIONS

	CHARACTERISTICS	METHODS
Solid content	50 %	-
Viscosity	Z-Z2 Gardner Holdt	-
Reduced viscosity (40% in Xylene)	F-H	-
Color	12 Gardner	-
Acid value	16 mg KOH/g	-

### OTHER CHARACTERISTICS<sup>1</sup>

	CHARACTERISTICS	METHODS
Solvent	Xylene/VM&P 66/34	-
Density	8 lbs/gal	-
Hydroxyl content	2.4 %	-
Hydroxyl number	79	-

<sup>1</sup>The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

### MARKETS

#### Coatings & Inks

- Industrial Coating
  - Automotive - OEM
  - General Industry

### PERFORMANCE BENEFITS

- Fast Tack Free Times
- Fast Through Dry
- Excellent Salt Spray Resistance
- Excellent Resistance to Gasoline and Moisture
- Can be Lacquered Top-coated in 5 to 10 Minutes

# CHEMPOL® 812-4102

## FORMULATION GUIDELINES

### RECOMMENDATIONS OF USE

Primer Coatings  
Drum Coatings  
Storage Tank Coatings  
Auto OEM Underhood Parts  
General Purpose Industrial Coatings

## PRODUCT SAFETY

Please refer to the corresponding Safety Data Sheet.

## STORAGE AND HANDLING

CHEMPOL® 812-4102 - Packaged products should be stored in a dry indoor location. The material should be stored in the original, unopened and undamaged container at storage temperatures not exceeding 85° F (30° C). Exposure to direct sunlight should be avoided. For assistance with the best practices for bulk shipment storage and handling contact Arkema.

**Arkema Coating Resins**  
410 Gregson Dr.  
Cary, NC 27511 – USA  
T +1 919 469 6700

**Headquarter: Arkema France**  
51, Esplanade du Général de Gaulle  
92800 Puteaux – France  
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.  
Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

[arkema.com](https://www.arkema.com)

