

TECHNICAL DATA SHEET

CHEMPOL® 900-0067

Stabilizer

PRODUCT APPLICATION DETAILS

CHEMPOL® 900-0067 is a UV stabilizer solution used to improve exterior coating performance. Improves yellowing resistance and gloss retention especially for Styrene/Acrylic concrete and auto refinish coatings. Use @ 1-2% on solids

SALES SPECIFICATIONS

	CHARACTERISTICS	METHODS
Solid content	20 %	-
Viscosity	<a gardner="" holdt<="" td=""><td>-</td>	-
Color	Yellow Gardner	-
Acid value	11 mg KOH/g	-

OTHER CHARACTERISTICS¹

	CHARACTERISTICS	METHODS
Solvent	Aromatic 100	-
Density	7.5 lbs/gal	-

^{&#}x27;The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

MARKETS

Coatings & Inks

- Architectural Coating
 - Exterior Wall
 - Primers
 - Specialty Coatings
- Flooring
 - Floor Polish & Floor Coatings

PERFORMANCE BENEFITS

- Improves yellowing resistance
- Improves gloss retention



Coating Resins - 2025-05-25 - Page: 2 / 2

CHEMPOL® 900-0067

FORMULATION GUIDELINES

RECOMMENDATIONS OF USE

Recommended use level; 1-2% on resin solids Stabilizer for Styrene/Acrylic concrete coatings Stabilizer for auto refinish coatings

PRODUCT SAFETY

Please refer to the corresponding Safety Data Sheet.

STORAGE AND HANDLING

CHEMPOL® 900-0067 - Packaged products should be stored in a dry indoor location. The material should be stored in the original, unopened and undamaged container at storage temperatures not exceeding 85° F (30° C). Exposure to direct sunlight should be avoided. For assistance with the best practices for bulk shipment storage and handling contact Arkema.

Arkema Coating Resins 410 Gregson Dr. Cary, NC 27511 – USA T +1 919 469 6700 Headquarter: Arkema France 51, Esplanade du Général de Gaulle 92800 Puteaux – France T +33 (0)1 49 00 80 80

