

# TECHNICAL DATA SHEET

ENCOR<sup>®</sup> 282

Vinylic Emulsion

## **PRODUCT APPLICATION DETAILS**

high performance general purpose vinyl acetate/ethylene (VAE) binder for architectural coatings.

# **SALES SPECIFICATIONS**

	CHARACTERISTICS	METHODS
Solid content	56.0 %	-
рН	4.5 - 5.5	-
Viscosity (#3 spindle @ 60 rpm. Brookfield LV)	<500 cP	-

# **OTHER CHARACTERISTICS<sup>1</sup>**

	CHARACTERISTICS	METHODS
Minimum film formation temperature	0 °C	-
Glass transition temperature (DSC)	11 °C	-
Density	8.8	-
Average particle size	400 nm	-

'The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

#### MARKETS Coatings & Inks

Architectural Coating

- Interior Wall
- Primers
- Trim



# **ENCOR® 282**

# **PRODUCT SAFETY**

Please refer to the corresponding Safety Data Sheet.

## **STORAGE AND HANDLING**

ENCOR® 282 - When storing and handling follow procedures recommended for polymer dispersions. Use corrosion resistant storage tanks and piping. Air-operated diaphragm pumps are preferred. Avoid temperature extremes. Do not freeze. Store between 40 to 90 °F (4 -32 °C). Packaged material should be stored indoors in a dry place in the original unopened and undamaged container. Exposure to direct sunlight should be avoided. The product is protected to prevent microbial deterioration during normal storage conditions; however, care should be taken to avoid accidental contamination during subsequent handling and processing. Bulk storage and handling practices are described in the Arkema Latex Storage and Handling Guide. For a copy of this guide contact Arkema.

Coating Resins - 2025-04-16 - Page: 2 / 2

**Arkema Coating Resins** 410 Gregson Dr. Cary, NC 27511 – USA T +1 919 469 6700

**Headquarter: Arkema France** 51, Esplanade du Général de Gaulle 92800 Puteaux – France T +33 (0)1 49 00 80 80

ARKEMA

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on https://www.arkema.com/global/en/products/product-safety/disclaimer/ which is incorporated herein by reference and made a part hereof. Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the

number 319 632 790

arkema.com