

TECHNICAL DATA SHEET

SNAP[®] 2709

Acrylic Emulsion

PRODUCT APPLICATION DETAILS

SNAP[®] 2709 is a low MFFT acrylic emulsion with a morphology specifically designed to allow an excellent film formation. It is particularly adapted to the formulation of trim enamels for exterior and interior applications.

SNAP[®] 2709 is formulated without alkylphenolethoxylates or formaldehyde.

SNAP[®] 2709 has been developed to be used as binder for both interior and exterior trim enamels. Its specific & controlled structure ensures a stable minimum film formation temperature as well as a very good film formation with no coalescing agent even at low temperatures.

In terms of film properties, SNAP[®] 2709 allows to get a coating exhibiting a good compromise of flexibility and hardness and a very good block resistance. The final properties of the coating are achieved extremely rapidly (within 24 hours of drying) and are stable with time as no coalescing agent (VOC or non VOC) is used. SNAP[®] 2709 is a binder of choice for durable exterior coatings.

SALES SPECIFICATIONS

	CHARACTERISTICS	METHODS
Solid content	44 - 46 %	ISO 3251
pH	7.5 - 8.5	ISO 976
Viscosity (Brookfield RVT , 20rpm) (23°C)	500 max mPa.s	ISO 2555

OTHER CHARACTERISTICS¹

	CHARACTERISTICS	METHODS
Stabilizing system	A / NI	
Minimum film formation temperature	5 °C	ISO 2115
Density	1.06 g/ml	ISO 2811
Average particle size	90 - 100 nm	ISO 13321

¹The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

MARKETS

Coatings & Inks

- Architectural Coating
 - Primers
 - Specialty Coatings
 - Stains
 - Trim

PERFORMANCE BENEFITS

- Excellent blocking resistance (even at high temperatures)
- Excellent hardness development
- Excellent wet and dry adhesion (especially onto aged alkyds)
- Excellent flexibility
- Easy controlled rheology
- Good pigment compatibility

FORMULATION GUIDELINES

RHEOLOGY

SNAP® 2709 is easy to formulate as its reactivity to thickeners is balanced and controlled. It is possible to achieve the desired rheological profile (more or less Newtonian) depending on the targeted application.

This controlled thickeners reactivity allows to optimise the levelling of SNAP® 2709-based paints and varnishes.

Rheology can be adjusted using associative thickeners such as HEUR thickeners : Polyurethane thickeners such as Coapur™ XS 22 ⁽¹⁾, Coapur™ 830W ⁽¹⁾, Coapur™ 2025 ⁽¹⁾ which are efficient ; Hydrophobically Modified PolyEther thickeners, e.g. Aquaflo® NHS 300 ⁽²⁾, Aquaflo® NMS 450 ⁽²⁾, are also suitable. HASE thickeners, such as Rheotech™ 2000 ⁽¹⁾ may also be suitable for satin paints.

OTHER ADDITIVES

Defoamers such as Byk®-022 ⁽³⁾, Byk®-028 ⁽³⁾, Byk®-093 ⁽³⁾, FoamStar® ST 2438 ⁽⁴⁾ as well as FoamStar® ED 2522 ⁽⁴⁾ are suitable. SNAP® 2709 formulations pH should be adjusted with ammonia : it is not recommended to formulate it with non-volatile amines or soda.

Notes: ⁽¹⁾ Coatex, ⁽²⁾ Ashland Specialty Ingredients, ⁽³⁾ Byk, ⁽⁴⁾ BASF

PRODUCT SAFETY

Please refer to the corresponding Safety Data Sheet.

STORAGE AND HANDLING

SNAP® 2709 should be stored indoors in the original, unopened and undamaged container, in a dry place at storage temperatures between 5°C and 30°C. Exposure to direct sunlight should be avoided. The product is protected to prevent any microbial deterioration during normal conditions of storage but care should be taken to avoid accidental contamination during subsequent handling and processing. In the above mentioned storage conditions the shelf life of the resin will be from the shipping date.

Shelf Life (Months): 6

Headquarter: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.

Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790