

TECHNICAL DATA SHEET

SYNOCURE® 9485 S 70

PRODUCT APPLICATION DETAILS

SYNOCURE® 9485 S 70 is an acrylic for use in topcoats where a non-isocyanate (NISO) curing system is needed, that has exterior durability, solvent resistance, hardness, adhesion, and color retention. Long pot lie. Very high gloss. Requires primer where good corrosion resistance is needed.

SALES SPECIFICATIONS

	CHARACTERISTICS	METHODS
Solid content	70 %	-
Viscosity	Z3-Z5 Gardner Holdt	-
Reduced viscosity (50% In Xylene)	F-I	
Color	6 Gardner	-
Acid value	18 mg KOH/g	-

OTHER CHARACTERISTICS¹

	CHARACTERISTICS	METHODS
Solvent	Xylene/PGMME 80/20	-
Glass transition temperature (DSC)	28 °C	-
Density	8.5 lbs/gal	-

¹The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

MARKETS

Coatings & Inks

- Industrial Coating
 - Automotive - OEM
 - General Industry
 - Protective And Marine Coating

SYNOCURE® 9485 S 70

PRODUCT SAFETY

Please refer to the corresponding Safety Data Sheet.

STORAGE AND HANDLING

SYNOCURE® 9485 S 70 should be stored indoors in the original, unopened and undamaged container, in a dry place at a temperature not exceeding 30°C. Exposure to direct sunlight should be avoided. In the above mentioned storage conditions the shelf life of the resin will be months from the shipping date.

Arkema Coating Resins
410 Gregson Dr.
Cary, NC 27511 – USA
T +1 919 469 6700

Headquarter: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.
Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790