

## TECHNICAL DATA SHEET

# SYNOLAC® 7500

*Very long oil alkyd*

### PRODUCT APPLICATION DETAILS

SYNOLAC® 7500 is a long oil length, high solid, oxidising alkyd. SYNOLAC® 7500 exhibits good penetration into wooden substrates and very smooth wiping feel. It has very good gloss and flexibility.

### SALES SPECIFICATIONS

	CHARACTERISTICS	METHODS
Solid content (125°C, %)	Min. 98	ISO 3251
Viscosity (25°C, Gardner)	X-Z	Gardner-Holdt
Color (Gardner)	Max. 8	ASTM D-1544
Acid value (mg KOH/g)	3 - 10	ISO 2114

### OTHER CHARACTERISTICS<sup>1</sup>

	CHARACTERISTICS	METHODS
Solvent	Nil	-
Density (25°C, g/mL)	0.99	-
Fatty acid type	Linseed Oil	-
Fatty acid content (%)	75	-

<sup>1</sup>The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

### MARKETS

#### Coatings & Inks

- Architectural Coating
  - Primers
  - Stains
- Industrial Coating
  - Wood Furniture
  - Wood Stains

### PERFORMANCE BENEFITS

- Good flexibility
- Excellent and easy wiping
- Excellent penetration into wood
- Excellent pigment wetting
- High pigment loading

# SYNOLAC® 7500

## FORMULATION GUIDELINES

### RECOMMENDATIONS FOR USE

As a sole binder, or in combination with suitable thixotropic alkyd resins, SYNOLAC® 7500 produces paints and stains with high solids content. It is most suitable for high solid wood primers.

For decorative paints, a mixture of Cobalt and Zirconium driers to give 0.05% Cobalt and 0.15% Zirconium expressed as metals on solid resin are recommended. Where drier absorption on pigment surfaces is a potential problem or in industrially polluted atmospheres, Calcium drier up to a maximum of 0.2% metal on solid resin can be used in addition. It is normal practice to add anti-skinning agent, and methyl ethyl ketoxime at 0.1% of the total paint is recommended.

### SOLUBILITY

Aromatic hydrocarbon — Complete  
Aliphatic Hydrocarbon — Complete  
Alcohol — Partial

### COMPATIBILITY

Long Oil Alkyd — Very Good  
Linseed Oil — Very Good  
Stand Oil — Very Good  
Medium Oil Alkyd — Partial  
Thixotropic Alkyd Resins — Good

## PRODUCT SAFETY

Please refer to the corresponding Safety Data Sheet.

## STORAGE AND HANDLING

SYNOLAC® 7500 should be stored indoors in the original, unopened and undamaged container, in a dry place at a temperature not exceeding 35°C. Exposure to direct sunlight should be avoided.

In the above mentioned storage conditions the shelf life of the resin will be 12 months.

**Arkema Coating Resins Malaysia**  
PLO 491, Jalan Keluli, Pasir Gudang  
Industrial Estate, 81700 Pasir Gudang,  
Johor – Malaysia  
T +60 7 253 6688

**Headquarter: Arkema France**  
420, rue d'Estienne d'Orves  
92705 Colombes Cedex – France  
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.

Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

**ARKEMA**