

TECHNICAL DATA SHEET

SYNOLAC® 8068 X 50 (Formely CHEMPOL® 809-3068)

PRODUCT APPLICATION DETAILS

 ${\tt SYNOLAC^{\circ}~8068~X~50~is~a~chain-stopped~soya~short~oil~alkyd~with~high~gloss,~superior~gloss}$ retention, and excellent salt spray resistance, for use in 2K urethane metal coatings.

SALES SPECIFICATIONS

	CHARACTERISTICS	METHODS
Solid content	50 %	-
Viscosity	T-W Gardner Holdt	-
Reduced viscosity (40% in Xylene)	B-D	-
Color	8 Gardner	-
Acid value	12 mg KOH/g	-

OTHER CHARACTERISTICS¹

	CHARACTERISTICS	METHODS
Solvent	Xylene	-
Density	8.3 lbs/gal	-
Hydroxyl content	3.5 %	-
Hydroxyl equivalent weight	480	-
Hydroxyl number	117	-

^{&#}x27;The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

MARKETS

Coatings & Inks

- · Industrial Coating
 - Automotive OEM
 - General Industry

PERFORMANCE BENEFITS

- High gloss
- Superior Florida gloss retention
- Good salt spray resistance Excellent resin for alkyd 2K urethane coatings



FORMULATION GUIDELINES

RECOMMENDATIONS OF USE

Agricultural and heavy equipment coatings Transportation finishes General industrial metal Machinery enamels

PRODUCT SAFETY

Please refer to the corresponding Safety Data Sheet.

STORAGE AND HANDLING

SYNOLAC® 8068 X 50 - Packaged products should be stored in a dry indoor location. The material should be stored in the original, unopened and undamaged container at storage temperatures not exceeding 85° F (30° C). Exposure to direct sunlight should be avoided. For assistance with the best practices for bulk shipment storage and handling contact Arkema.

> **Arkema Coating Resins** 410 Gregson Dr. Cary, NC 27511 – USA T +1 919 469 6700

Headquarters: Arkema France 51, Esplanade du Général de Gaulle 92800 Puteaux – France T +33 (0)1 49 00 80 80

