

ENCOR® 9215 LATEX

COATER-READY, HIGH-SOLIDS, TACKIFIED ACRYLIC LATEX
FOR PERMANENT PAPER LABELS



Product Benefits

ENCOR® 9215 latex is a tackified acrylic adhesive formulated for high-speed slot-die and curtain coaters. This adhesive is designed for general purpose paper labels that require excellent adhesion to corrugated cardboard.

Polymer Type

Acrylic

Performance Benefits

- Good balance of peel, tack and cohesive strength
- High coating speeds
- Adhesion to corrugated cardboard
- Excellent converting properties
- Conformance to FDA 21CFR175.105

Typical Physical Properties¹

Total Solids, % by weight	60
Weight per Gallon, lb Latex	8.6
Polymer	9.3
pH Value	7.5
Particle Size, microns	0.4
Viscosity, Brookfield, cP, #2 LVT at 50 rpm, 25±1°C	600
Glass Transition Temperature (T _g), midpoint, °C	-38

Typical Adhesive Properties²

180° Peel, 30 min dwell on stainless steel, pli	4
180° Peel, 30 min dwell on HDPE, pli	3.5
Loop Tack on stainless steel, psi	3.3
Shear Resistance, hours, on stainless steel, (1"×1", 1 kg)	>50h

Tested on 2-mil PET backing at a coat weight of 1.2 – 1.4 g/100 in², 73° F, 55% R

¹The physical property data listed are considered to be typical properties, not specifications

²The adhesive property data listed are considered to be typical properties, not specifications.



ENCOR® 9215 LATEX

COATER-READY, HIGH-SOLIDS, TACKIFIED ACRYLIC LATEX FOR PERMANENT PAPER LABELS

Adhesive Performance Assessment

(arbitrary scale: 5 = Best)




Figure 1 illustrates the balanced adhesion characteristics and superior coating speeds possible with ENCOR® 9215 latex. *

*All performance claims in any application should be independently confirmed by the user.

ENCOR® 9215 LATEX

COATER-READY, HIGH-SOLIDS, TACKIFIED ACRYLIC LATEX FOR PERMANENT PAPER LABELS

Product Safety

Before handling the materials listed in this bulletin, read and understand the product SDS (Safety Data Sheet) for additional information on personal protective equipment and for safety, health and environmental information. For environmental, safety and toxicological information, contact our Customer Service Department at 1-866-837-5532 to find an SDS, or visit our web site: coatingresins-arkema.com

No chemical should be used as or in a food, drug, medical device, or cosmetic, or in a product or process in which it may contact a food, drug, medical device, or cosmetic until the user has determined the suitability and legality of the use. Since government regulations and use conditions are subject to change, it is the user's responsibility to determine that this information is appropriate and suitable under current, applicable laws and regulations.

Coating Resins – Arkema requests that the customer read, understand, and comply with the information contained in this publication and the current SDS(s). The customer should furnish the information in this publication to its employees, contractors, and customers, or any other users of the product(s), and request that they do the same.

Storage and Handling

Follow procedures typically recommended for polymer dispersions. Use corrosion-resistant storage tanks and piping. Air-operated diaphragm pumps are preferred.

Packaged material should be stored indoors in the original unopened and undamaged container, in a dry place. Exposure to direct sunlight should be avoided.

Avoid extreme temperatures. Do not freeze; store between 40-90°F (4-32°C).

For more details, refer to "Storage and Handling of Arkema Coating Resins Products – A Basic Guide".



Coating Resins – Arkema
410 Gregson Dr.
Cary, NC 27511
Telephone:
1.800.777.8227

IMPORTANT: The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, Arkema expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement.

DISCLAIMER: Please consult Arkema's disclaimer regarding the use of Arkema's products on <http://www.arkema.com/en/products/product-safety/disclaimer/index.html>

Visit our website:
coatingresins-arkema.com

© 2019 Arkema Inc. All rights reserved. Revised 3/19
ENCOR® is a registered trademark of Arkema Inc.